

SPECIFICATION

Electronic Version 1.2.8

Stylesheet Version 1.0

[CONFIGURABLE ROOF RACK SYSTEM]

Cross Reference to Related Applications

This application claims priority from United States Provisional Patent Application Serial No. 60/259,005 filed on December 29, 2000.

Background of Invention

[0001] The present invention relates generally to an automotive roof rack system and more particularly to an automotive roof rack system with increased functionality.

[0002] Considerable effort has been exhausted by automotive engineers in an attempt to increase the utility of modern automotive designs. Although mere transportation of occupants still remains a primary objective, the modern automotive vehicle is often designed to provide a greater range of utilities. Design considerations such as customer convenience, ease of use, and increased functionality contribute significant impetus into the ever-evolving automotive designs. One particular area of design, requiring such considerations, and important to the increased utility of the vehicle, is the area of vehicle storage capacity.

[0003] Improvements to vehicle storage capacity have taken on a wide variety of forms. One set of improvements has led to an increase in storage capacity within the vehicle compartment. Although vehicles such as SUVs and minivans may provide such increased storage within the vehicle compartment, vehicle owners often prefer to utilize this space to increase passenger occupant capacity rather than for storage. Other, and possibly more traditional, storage techniques utilize separate compartments often positioned in the rear of the vehicle. These areas, commonly referred to as trunks, provide storage isolated from the passenger compartment. The size of these compartments as well as the presence of a deck lid, however, often prevents their use for storage and transporting oversized objects. There is, therefore, often a need to store and transport oversized objects or a large quantity of objects without interfering with passenger

occupancy areas. This ability is commonly not afforded by trunk space.

[0004] One traditional approach to providing such storage has been through the use of a roof rack. The use of roof racks dates back considerably in the history of automotive design. Their use allows occupants to store and transport objects on the roof of the vehicle without interfering with passenger occupancy and without the limitations of common trunk designs. Although their position on the roof of the vehicle can provide occupants with considerably storage, their very position often proves detrimental to the accessibility necessary to load and unload the stowed items. The advent of larger vehicles such as SUVs, vans, and minivans has exacerbated the accessibility problems often associated with present roof rack designs. Even relatively tall individuals can have difficulty loading and unloading roof racks on such large vehicles. An improvement to the accessibility of roof rack systems would be highly beneficial and would serve to increase consumer convenience and satisfaction.

[0005] In addition to problems arising involving accessibility, present roof rack systems can suffer from additional limitations. Often, a roof rack structure designed to accommodate the storage of smaller items may prove incompatible with the storage of larger items such as kayaks, bikes, and other large objects. One standard approach to the storage of small items has been the formation of a basket within the roof rack system. Although these baskets have proven highly convenient, it is also known that they can interfere with the mounting of larger storage items to the roof rack system. One solution has been to provide basket systems that may be mounted and unmounted from the roof rack system. This commonly requires assembly and disassembly procedures that can reduce the convenience of the roof rack system. In addition, removal of portions of the roof rack system may require storage of rack parts and, therefore, may be impractical in some scenarios. A more flexible roof rack system that could accommodate both small and large storage objects without requiring disassembly of the roof rack system would be highly beneficial. It would, therefore, be highly desirable to have a roof rack system with improved accessibility and increased flexibility to accommodate both large and small storage objects.

Summary of Invention

[0006] It is, therefore, an object of the present invention to provide an automotive roof rack system with improved accessibility and improved flexibility.

[0007]

sub c17
~~In accordance with the objects of the present invention, an automotive roof rack system is provided. The automotive roof rack system includes at least one storage surface having a first~~

position, generally coincident to the roof of the vehicle, and a second position, generally coincident to the side of the vehicle. The at least one storage surface is movable between the first position and the second position to provide an automotive roof rack system with improved accessibility and increased flexibility.

[0008] Other objects and features of the present invention will become apparent when viewed in light of the detailed description of the preferred embodiment when taken in conjunction with the attached drawings and appended claims.

Brief Description of Drawings

[0009] FIGURE 1 is an illustration of an automotive roof rack system in accordance with the present invention, the roof rack system shown in a stored first position;

[0010] FIGURE 2 is an illustration of an embodiment of an automotive roof rack system in accordance with the present invention, the automotive roof rack system shown in a deployed second position; and

[0011] FIGURE 3 is an illustration of an embodiment of an automotive roof rack system in accordance with the present invention, the automotive roof rack system shown in an alternate deployed position; and

[0012] FIGURE 4 is an illustration of an embodiment of an automotive roof rack in accordance with the present invention, the automotive roof rack system shown in a collapsed position.

Detailed Description

[0013] Referring now to Figure 1 which is an illustration of an embodiment of a roof rack system 10 in accordance with the present invention. The roof rack system 10 is intended for use on an automobile 12 having a roof portion 14 and a side portion 16. Although the roof rack system 10 is illustrated in a particular position in configuration on the automobile 12, it should be understood that a wide variety of positions and configurations are contemplated by the present invention.

[0014] ⁵⁰²¹ The roof rack system 10 includes at least one storage surface 20. The use of a storage surface 20 for mounting objects for transport is well known in the prior art. The at least one storage surface 20 is movable between a first position 22, where the at least one storage surface 20 is generally coincident to the roof portion 14 of the automobile 12, and a second position 24 (see Figure 2), where the at least one storage surface 20 is generally parallel to the side portion 16 of

the automobile 12. The capability of moving the at least one storage surface 20 from the first position 22 to the second position 24 provides a variety of benefits.

[0015] One set of benefits realized by the present invention involves accessibility of the roof rack system 10. In the prior art, when a storage surface was positioned on the roof portion 14 of the automobile 12, it was often difficult for many users to access the storage area due to the height of the vehicle 12. Often users were required to balance themselves within door frames or on tailgates in an effort to reach the roof portion 14. Even then, often portions of the storage surface 20 would be out of the reach of some users. The present invention improves upon on the accessibility of these designs by having a storage surface 20 that is movable between the first position 22 and the second position 24. Objects may be attached and detached from the at least one storage surface 20 while the at least one storage surface 20 is in the second position 24, allowing convenient and easy access to the at least one storage surface 20 from the side of the vehicle. The at least one storage surface 20 may then be moved back into the first position 22 for transport. In another scenario, the at least one storage surface 20 may be left in the second position 24 during transport. This provides a convenient mounting surface for oversized objects to be secured onto the side of the vehicle during transport. This further improves on accessibility since heavy and oversized objects need not be lifted to the height of the roof portion 14 of the vehicle 12 but only to the height of the side portion 16.

[0016] In addition to the improvements in accessibility, the present invention provides flexibility of use not often found in present roof rack designs. As has been discussed, the present invention can provide more storage on the side portion of the vehicle 16 as well as the roof portion 14. Additionally, by moving the at least one storage surface 20 from the first position 22 to the second position 24, the roof rack system 10 may be more suitable for the mounting of oversized objects, such as skis, boats, or bikes, on the roof portion 14 of the automobile 12. In one embodiment, the roof rack system 10 further includes a plurality of collapsible rails 26. The plurality of collapsible rails 26 when in the raised position 28 provide basket style support for objects mounted on the at least one storage surface 20 (see Figure 1). When the plurality of collapsible rails 26 are moved into the collapsed position 29 and the at least one storage surface 20 is moved into the second position 24 (see Figure 3), the roof portion 14 of the automobile 12 is cleared of any obstructions that may interfere with the mounting of oversized objects to the roof 14 of the vehicle 12. In this scenario, the at least one storage surface 20 is moved into the second position 24 to provide additional storage on the side portion 16 of the vehicle 12 while the roof portion 14 is cleared for oversized objects. In an alternate embodiment, the at least one

storage surface 20 may be left in the first position 22 and the plurality of collapsible rails 26 may be folded down to provide a roof portion 14 cleared of obstructions (see Figure 4).

[0017]

sub 37
Although the roof rack system 10 has thus far been described generically, it is contemplated that the roof rack system 10 may be formed in a variety of specific embodiments. In one such embodiment, the at least one storage surface 20 includes a right storage surface 30 and a left storage surface 32. Although the left storage surface 32 and the right storage surface 30 may be formed in a variety of fashions, in one embodiment, they include a plurality of slat elements 34 positioned mounted between track elements 36. The track elements 36 travel along guide elements 38 to allow the storage surface 20 to move from the first position 22 into the second position 24. The track elements 36 may also include securing slots 40 to provide fastening points for securing objects to the storage surface 20. *two?*

[0018]

only one shown
The roof rack system 10 may additionally include a left end rail element 42 and a right end rail element 44 mounted on the left storage surface 32 and the right storage surface 30, respectively. The left end rail element 42 and the right end rail element 44 serve a dual purpose. When the storage surface 20 is in the first position 22, the left end rail element 42 and the right end rail element 44 are positioned in conjunction with a plurality of collapsible rails 26 to form a basket 46 on the roof portion 14 of the vehicle 12. The basket 46 helps retain objects stored on the roof portion 14 of the vehicle 12 during transportation. Additionally, when the storage surface 20 is in the second position 24, the left end rail element 42 and the right end rail element 44 can serve as a base support for objects mounted on the side portion 16 of the vehicle. In other embodiments, however, the left end rail element 42 and the right end rail element 44 may be collapsed onto the storage surface 20 when in the second position 24 to minimize the width profile of the automobile 12.

[0019]

could be
The roof rack system 10 may further include a plurality of mounting elements 50. Although a variety of configurations are contemplated, in one embodiment the use of three mounting elements 50 is contemplated. *two* It is contemplated that the mounting elements 50 may include latching areas 52. The latching areas 52 may be utilized as a convenient location to attach bungee cords or other securing straps commonly utilized to hold objects on the roof rack system 10. The present invention may further include a locking mechanism 54 for securing the storage surface 20 in the second position 24. Although a variety of locking elements 54 are contemplated by the present invention, in one embodiment the locking element 54 is a pivoting lock that can remain flush with the side portion 16 of the vehicle 12 while the storage position 20 is in the first

gute
A3

While the invention has been understood that the specific methods and apparatus described are merely illustrative of the principles of the invention, other methods and apparatus described and defined by the appended claims are within the scope of the invention.

1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399</
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	--------